


C.J. ANDERSON & CO. *Magna-Track Selector*



MAGNA-TRACK
SELECTOR HEAD & HOLDER
(SIDE VIEW)



MAGNA-TRACK
SELECTOR HEAD & HOLDER
(FRONT VIEW)

IMPORTANT WARNING

Technical Assistance - CJA staff personnel are available to answer any questions concerning the use or application of CJA products. However, any field changes made to the products are the sole responsibility of the user, unless authorized by CJA in the form of revised wiring diagrams or technical bulletins.

Maintenance of Products - All CJA products require scheduled periodic inspections, adjustments, lubrication and other routine maintenance actions. Non-performance of maintenance will nullify the product warranty.

LIMITS OF LIABILITY CJA's entire liability and the purchaser's exclusive remedy shall be as follows: In all situations, including performance or non-performance of the material ordered, the purchaser's remedy is that provided under the warranty provision. CJA's liability for loss of or damage to purchaser for any cause whatsoever and regardless of the form of action, contract or in tort, including negligence, shall be limited to the price of the part on which such liability is based. CJA will not be liable for any injury, special, direct or consequential damage, loss of time, profit or other losses, labor charges, repairs, expenses or other cost arising out of the incorrect use of, or the inability of the purchaser to use the product. Correction of any defects by repair or replacement by CJA shall constitute fulfillment of all obligations to the purchaser. In no event will CJA be responsible for any loss, damage or delay. In no event will CJA be liable for any damages caused by purchaser or for any lost profits or other special, incidental or consequential damages. CJA products are only warranted to function as designed and manufactured. If the product does not meet the purchasers' expectations or standards, the purchaser is still obligated to pay for the product in full.

WARRANTY - All CJA products are warranted to the original purchaser to be free from defects in material and workmanship for a period of one year from the date of shipment, provided they are (1) paid for, (2) installed as designed and (3) used for the purpose intended. This warranty will only be effective after notification from the purchaser of a product defect, return of the part freight prepaid, and after CJA inspection proves the part to be defective. CJA's total obligation under this warranty is to repair or replace free of charge defective products. If the product is determined to be out of warranty an estimate to repair will be sent to the purchaser.

Before using or furnishing to another for their use, the purchaser shall determine the suitability of the product for its intended use and purchaser assumes all risks and liabilities in connection therewith. Any unauthorized repairs or adjustments shall cancel this warranty and shall relieve the company from any further responsibility.

FOR A COMPLETE COPY OF OUR TERMS AND CONDITIONS PLEASE CALL 1-800-252-1910.

Item#: 636-530 Rev. A.

1

Mount Top Tape Guide - Install To Rail Using Strut & Brackets



Ensure that top tape mounting bracket is installed high enough that roller guides do not strike unit.

This unit is full adjustable.

2

Mount Bottom Tape Guide Install To Rail Using Strut & Brackets



3

Mount Stainless Steel Tape To Top Tape Guide Holder



Slowly move elevator or unroll tape down the shaft way to the pit. Note that if tape kinks it will not work

4

Connect Bottom of Tape to Bottom Tape Guide Holder & Tension



Make certain that pushbutton is centered in hole to prevent dust and moisture from entering station. Do NOT over tighten and make sure that the tape is lined up.

5

Remove Tape Guides From Tape Head



Note that you'll need to remove the tape guides to insert the tape.

6

Install Selector Head & Control Box - Wire To Junction Box



*Note that the bracket that the top tape head is not shown in this photograph.
Wire Control Box with 110VAC Power to board with transformer on it.*

MAINTENANCE: - As with all moving parts this operator may require maintenance. The design and construction is intended for wet and dusty locations. These location may require that lubrication to the moving contact block parts be performed on regular basis. It is up to the elevator technician to determine how often to lubricate the moving components based on the environmental conditions and how severe they are.

7

Magnet Layout & Sensor Layout On Tape Head - Note Facing Stainless Steel Tape Where Magnets Will Mount

Magnet Layout - Without Encoding Feedback
 While CJA Elevator Control Systems do not come equipped with floor encoding feedback due to the limitations with meeting the explosion proof design requirements. Five sensors come standard on each selector system. Please consult your selector magnet layout from your controller manufacturer as to where magnets need to be placed in order to accomplish floor encoding. Cut magnets shorter if required or stack magnets to make them longer if necessary.

PLEASE NOTE THAT THIS SELECTOR SYSTEM REQUIRES 110VAC POWER TO OPERATE. DEPENDING ON THE MODEL, ENCODING OR NON ENCODING IT PROVIDES 5-10 DRY CONTACTS TO CONNECT TO YOUR CONTROLLER. THESE CONTACTS ARE RATED 250 VOLTS AC AT 12 AMP AND 30 VOLTS DC AT 12 AMP. THE RELAY COIL VOLTAGE IS 12 VOLTS DC

PLEASE CONSULT YOUR CONTROLLER PRINT FOR SPECIFIC CONNECTION INFORMATION.



Door Zone Magnet Positioning
 Using the magnet layout comb align with the edge of tape. It will provide a guide for magnet layout of each track.

DOOR ZONE MAGNET – In the center lane or the one with three sensors place magnet on tape so that when elevator is at the floor landing only the Door Zone Sensor is active.

Slow Down Magnet Positioning
 Using the magnet layout comb align with the edge of tape. It will provide a guide for magnet layout of each track.

DOWN/DOWN SLOWDOWN MAGNET – In the down slow-down row, or track 1, measure from the center of the leveling magnet up to the slowdown distance required for your job. We recommend 6” away from the floor for ever 25 feet of car speed. Consult with your controller manufacturer for additional assistance.

Note that the higher speed elevator the longer the slow down magnets need to be. Wire Unit according to wiring schematic on back of cover.





Trouble Shooting Your Selector

The Magna Track Selector System has been an active product of C.J. Anderson since 1995.

The list of issues below are ones that we've been able to document.

Problem: No LED's Light Up When Magnets are mounted

- Check Incoming Voltage to Unit, The Master board must have 110vac connected to it to power the unit. The Master board is the one with the transformer on it.

- Check to make sure magnets are still active. Extreme heat and cold effect how strong a magnet is. You may need to double up or change out magnets.

Problem: Having Trouble Figuring Out Where To Place Magnets --

- Consult the selector layout sheet that was provided by your controller manufacturer. Most have a wiring/layout diagram that shows what sensors should be active and at which floors. You'll need to transpose that information using the sensors of the Magna-Track.

Problem: Tape Guides Excessively Wearing

- The nylon tape guides will need to be replaced over time. Installing it outside is not recommended. Due to wind and excessive flapping we recommend that you install a switch type system to control leveling functions.

REMEMBER THIS DEVICE PROVIDES FEED BACK TO THE CONTROLLER FOR SLOW DOWN, LEVELING AND DOOR ZONE FUNCTIONS. THEY NEED TO BE SET UP BY THE MECHANIC SO THAT IT PROVIDES THE CORRECT FEED BACK THE ELEVATOR CONTROLLER REQUIRES.



Replacement Parts

REPLACEMENT COMPONENTS

636-514	Tape Guide Each (4 req.)
636-517	Magna-Track Magnets
636-543	Control Board
636-516	Selector Tape 3" Wide x feet required

Need Replacement Parts?

Visit <http://www.cjanderson.com/elevatorselectorsystems.aspx> and you can view all that are available! Or give us a call at 1-800-252-1910!



C.J. ANDERSON

& C O M P A N Y

Helping You One Floor At A Time. Since 1910!

C.J. ANDERSON & COMPANY

4751 N. Olcott Avenue
Harwood Heights, IL 60706

Phone: 1-800-252-1910

Fax: 1-708-867-5467

www.cjanderson.com